



Water to Air Heat Exchanger Radiators

PART #	RAD SIZE	ROWS	GALLONS PER MINUTE	CUBIC FEET PER MINUTE	ENTERING WATER TEMP	LEAVING WATER TEMP	AIR PRESSURE DROP	WATER PRESSURE DROP	BTU PER HOUR
89026	12 X 14	2	3	650	140	122.7	0.29	2.89	25,520
	12 X 14	2	3	650	180	153.5	0.29	2.68	38,704
89027	17 X 20	2	6	1200	140	123.7	0.25	3.01	48,160
	17 X 20	2	6	1200	180	154.4	0.25	2.79	74,600
89028	17 X 20	3	6	1200	140	120.5	0.37	0.67	57,602
	17 X 20	3	6	1200	180	149.4	0.37	0.62	89,593
890281	18 X 18	3	6	1200	140	125.2	0.27	2.80	43,660
	18 X 18	3	6	1200	180	156.3	0.27	2.70	69,460
89029	23 X 24	3	6	1850	140	110.9	0.36	2.36	86,175
	23 X 24	3	6	1850	180	134.5	0.36	1.96	133,519
890291	36 X 36	2	6	6000	140	98.2	0.14	6.08	126,308
	36 X 36	2	6	6000	180	113.1	0.14	6.08	200,536


FIGURES ARE BASED ON ENTERING AIR TEMPERATURE OF 70 DEGREES F.




17"x20" 2 Row Radiator
(1/2" FTG Solder Connection)
89027



17"x20" 3 Row Radiator
(1" FTG Solder Connection)
89028



23"x24" 3 Row Radiator
(1" FTG Solder Connection)
89029



36"x36" 2 Row Radiator
(3/4" FTG Solder Connection)
890291